Series		New Generation NEW				Old Generation			
	1 Vo	SKM10W8	SKMW15W8	SKMW20W8	SKMW30W8	SKM10	SKMW15	SKMW20	SKMW30
	2 Vo	DKM10W8	DKMW15W8	DKMW20W8	DKMW30W8	DKM10	DKMW15	DKMW20	DKMW30
Wattage		10W	15W	20W	30W	10W	15W	20W	30W
Input Voltage (Vdc)		8 : 1 12V, 24V, 48V (9~75V)				2 : 1 5V (4.7~9V) 12V (9~18V) 24V (18~36V) 48V (36~72V)	4 : 1 12V , 24V (9~36V) 24V , 48V (18~75V)		
Output Voltage (Vdc)	1 Vo	3.3V, 5V, 12V, 15V 24V (SKMW15W8 only)				3.3V, 5V, 12V, 15V		5V, 12V, 15V	
	2 Vo	±5V, ±12V, ±15V		±12V, ±15V		±5V, ±12V, ±15V		±12V, ±15V	
Operating Temp.		-40~+90℃				-40~+85℃			
I/O Isolation		3KVdc		1.5KVdc		1.5KVdc	3KVdc	1.5KVdc	
Protection		Short circuit / Overload / Over voltage / Input under voltage Over temperature (SKMW / DKMW30W8 only)				Short circuit / Overload / Over voltage / Input under voltage Over temperature (SKMW / DKMW30 only)			
Dimensions (LxWxH)		25.4 x 25.4 x 10.2 mm (1" x 1" x 0.4")				25.4 x 25.4 x 10.2 mm (1" x 1" x 0.4")			
Safety Certification		EAC, CE, UKCA				EAC, CE, UKCA			
Warranty		3 years				3 years			

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000