Series		New Generation NEW					Old Generation				
	1 Vo	SKE10W8	SKA15W8	SKA20W8	SKM30W8	SKM50W8	SKE10	SKA15	SKA20	SKM30-N	SKM50
	2 Vo	DKE10W8	DKA15W8	DKA20W8	DKM30W8	-	DKE10	DKA15	-	DKM30-N	-
Wattage		10W	15W	20W	30W	50W	10W	15W	20W	30W	50W
Inout Voltage (Vdc)		8 : 1 12V、24V、48V (9~75V)					2 : 1 12V (9~18V) 24V (18~36V) 48V (36~72V)			4 : 1 12V 、24V (9~36V) 24V 、48V (18~75V)	2 : 1 12V (9~18V) 24V (18~36V) 48V (36~72V)
Output Voltage (Vdc)	1 Vo	3.3V、5V、12V、15V 9V (SKE10W8、SKMW15W8 only) 24V (expect SKM50W8)					3.3V (SKA15 only)、5V、12V、15V、24V (SKE10 only)				
	2 Vo	±5V、±12V、±15V		±12V、±15V		-	±5V、±12V、±15V ±24V (DKE10 only)		-	±12V、±15V	-
Operating Temp.		-40~+90℃					-25~+71℃	-40~+71℃	-40~+85℃	-40~+90℃	-40~+75℃
I/O Isolation		3KVdc					1.5KVdc			3KVdc	1.5KVdc
Protection		Short circuit / Overload / Over voltage / Input under voltage					Short circuit / Overload		Short circuit / Overload / Over voltage / Input under voltage		
Dimensions (LxWxH)		50.8 x 25.4 x 11.2 mm (2" x 1" x 0.44")				50.8 x 25.4 x 13.7 mm (2" x 1" x 0.54")	50.8 x 25.4 x 11.2 mm (2" x 1" x 0.44")				50.8 x 25.4 x 13.7 mm (1" x 1" x 0.54")
Safety Certification		EAC、CE、UKCA					EAC、CE、UKCA、FCC				
Warranty		3 years					2 years			3 years	2 years