Series		New Generation new					Old Generation				
	1 Vo	SCWN03W8	SCWN06W8	SCW08W8	SCW12W8	SCW20W8	SCWN03	SCWN06	SCW08	SCW12	SCW20
	2 Vo	DCWN03W8	DCWN06W8	DCW08W8	DCW12W8	DCW20W8	DCWN03	DCWN06	DCW08	DCW12	N.A
Power		3W	6W	8W	12W	20W	3W	6W	8W	12W	20W
Input (Vdc)		8 : 1 12V、24V、48V (9~75V)					2 : 1 5V (4.5~9V , only on SCWN03/DCWN03) 12V (9~18V) 24V (18~36V) 48V (36~72V)				2 : 1 12V (9~18V) 24V (18~36V) 48V (36~75V)
Output (Vdc)	1 Vo	3.3V、5V、9V、12V、15V (9V only on 8W/ 12W models)					3.3V、5V、12V、15V		5V、12V、15V		
	2 Vo	± 5V、±12V、±15V					± 5V、±12V、±15V				N.A
Operation Temp.		-40~+95℃		-40~+90℃	-40~+85℃	-40~+95℃	-40~+90℃		-40~+71℃		-40~+80℃
I/O isolation		3KVdc					3KVdc		1.5KVdc		
Protection		short circuit, overload, under-voltage lockout (UVLO) and over-voltage lockout (OVLO)					short circuit, overload, under-voltage lockout (UVLO)		short circuit, overload		
Dimensions (LxWxH)		31.8 x 20.3 x 10.2 mm		31.8 x 20.3 x 12.2 mm			31.8 x 20.3 x 10.2 mm		31.8 x 20.3 x 12.2 mm		
Safety Certification		EAC、CE 、UKCA					EAC、CE 、UKCA				
Warranty		3 years					3 years		2 years		3 years

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000