
1500W High Reliable Fanless Design with Conduction-Cooling Power Supply UHP-1500 series

User's Manual Click Me

Video Click Me



PMBus Power Management. Defined.

UL62368-1 BS EN/EN62368-1 TPTC004 IEC62368-1

Household Automate Industrial Security Network Telecom

Features

- 90 ~ 264Vac input with PFC
- Slim and Low profile (41mm)
- Fanless and conduction-cooled design
- Output voltage 50~120% and constant current 20~100% programmable
- Built-in PMBus or CANBus protocol
- Protections: Short circuit / Overload / Over voltage / Over temperature
- -30~+70℃ working temperature
- Built-in remote ON-OFF control
- DC OK active signal
- Operating altitude up to 5000 meter (Note.8)
- LED indicator for power on
- 5 years warranty

Applications

- Industrial automation machinery
- Industrial control system
- Mechanical and electrical equipment
- Electronic instruments, equipment or apparatus
- Test and measurement instrument
- Laser related machine
- Charging related equipment
- Household appliances
- Power Sourcing Equipment of PoE (48V model: DC O/P range 48~57.6V)

GTIN CODE

MW Search: https://www.meanwell.com/serviceGTIN.aspx

Description

UHP-1500 series is a 1500W single-output slim type power supply with 41mm of low profile design. Adopting the full range 90~264Vac input, the entire series provides an output voltage line of 24V and 48V. In addition to the high efficiency up to 96%, that the whole series operates from -30℃ ~ +70℃ under air convection without fan. UHP-1500 has the complete protection functions and 5G anti-vibration capability; It is complied with the international safety regulations such as DEKRA BS EN/EN62368-1, UL62368-1. UHP-1500 series serves as a high performance power supply solution for various industrial applications.

Model Encoding

UHP - 1500 - 24 ☐

- ☐ Communication protocol
- 24 Output voltage(24V/48V)
- 1500 Rated wattage
- UHP Series name

Type	Communication Protocol	Note
Blank	CANBus protocol	In Stock
PM	PMBus protocol	In Stock

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

SPECIFICATION

MODEL		UHP-1500-24□	UHP-1500-48□
OUTPUT	DC VOLTAGE	24V	48V
	RATED CURRENT	62.5A	31.5A
	RATED POWER	1500W	1512W
	RIPPLE & NOISE (max.) Note.2	240mVp-p	350mVp-p
	VOLTAGE ADJ. RANGE	By built-in potentiometer, SVR	
		24 ~ 28.8V	48 ~ 57.6V
	VOLTAGE TOLERANCE Note.3	±1.0%	±1.0%
	LINE REGULATION	±0.5%	±0.5%
	LOAD REGULATION	±0.5%	±0.5%
	SETUP, RISE TIME Note.4	1800ms, 60ms/230Vac 1800ms, 60ms/115Vac at full load	
	HOLD UP TIME (Typ.) Note.4	16ms/230Vac at 75% load 10ms/230Vac at full load ; 16ms/115Vac at 75% load 10ms/115Vac at full load	
INPUT	VOLTAGE RANGE Note.4	90 ~ 264Vac 250 ~ 370Vdc	
	FREQUENCY RANGE	47 ~ 63Hz	
	POWER FACTOR (Typ.) Note.4	PF≥0.95/230Vac PF≥0.99/115Vac at full load	
	EFFICIENCY (Typ.)	95%	96%
	AC CURRENT (Typ.)	11A/115Vac 8A/230Vac	
	INRUSH CURRENT (Typ.)	Cold start 30A/115Vac 60A/230Vac	
	LEAKAGE CURRENT	<0.75mA / 240Vac	
PROTECTION	OVERLOAD	105~125% rated current	
		Protection type : Constant current limiting, shut down O/P voltage after 5 sec. After O/P voltage falls, re-power on to recover	
	SHORT CIRCUIT	Constant current limiting, unit will shutdown after 5 sec, re-power on to recover.	
	OVER VOLTAGE	30 ~ 35V	60 ~ 67V
		Protection type :Shut down O/P voltage,re-power on to recover	
	OVER TEMPERATURE	Protection type :Shut down O/P voltage, recovers automatically after temperature goes down	
FUNCTION	OUTPUT VOLTAGE PROGRAMMABLE(PV) Note 5	Adjustment of output voltage is allowable to 50 ~ 120% of nominal output voltage Please refer to the Function Manual.	
	OUTPUT CURRENT PROGRAMMABLE(PC) Note 5	Adjustment of constant current level is allowable to 20 ~ 100% of rated current. Please refer to the Function Manual.	
	REMOTE ON/OFF CONTROL	Power ON : Short circuit Power OFF : Open circuit	
	AUXILIARY POWER	12V @ 0.4A tolerance ±10%, ripple=150mVp-p	
	DC-OK SIGNAL	The TTL signal out, PSU turn on = 4.4 ~ 5.5Vdc ; PSU turn off = -0.5 ~ 0.5Vdc. Please refer to the Function Manual.	
ENVIRONMENT	WORKING TEMP.	-30 ~ +70℃ (Refer to "Derating Curve")	
	WORKING HUMIDITY	20 ~ 90% RH non-condensing	
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 10 ~ 95% RH non-condensing	
	TEMP. COEFFICIENT	±0.03%/℃ (0 ~ 50℃)	
	VIBRATION	10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes	
SAFETY & EMC (Note.7)	SAFETY STANDARDS	UL62368-1, DEKRA BS EN/EN62368-1, EAC TP TC 004 approved	
	WITHSTAND VOLTAGE	I/P-O/P:3.75KVac I/P-FG:2KVac O/P-FG:1.25KVac	
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG,O/P-FG:100M Ohms/500Vdc/25℃/ 70%RH	
	EMC EMISSION	**Parameter**	**Standard** / **Test Level / Note**
		Conducted	BS EN/EN55032 (CISPR32) / Class B
		Radiated	BS EN/EN55032 (CISPR32) / Class A
		Harmonic Current	BS EN/EN61000-3-2 / Class A
		Voltage Flicker	BS EN/EN61000-3-3 / -----
	EMC IMMUNITY	BS EN/EN55035, BS EN/EN61000-6-2	
		Parameter	**Standard** / **Test Level / Note**
		ESD	BS EN/EN61000-4-2 / Level 3, 8KV air ; Level 2, 4KV contact
		Radiated	BS EN/EN61000-4-3 / Level 3
		EFT / Burst	BS EN/EN61000-4-4 / Level 3
		Surge	BS EN/EN61000-6-2 / 2KV/Line-Line 4KV/Line-Earth
		Conducted	BS EN/EN61000-4-6 / Level 3
		Magnetic Field	BS EN/EN61000-4-8 / Level 4
		Voltage Dips and Interruptions	BS EN/EN61000-4-11 / >95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods
OTHERS	MTBF	535.4K hrs min. Telcordia SR-332 (Bellcore) ; 56.7K hrs min. MIL-HDBK-217F (25℃)	
	DIMENSION	**290*140*41mm (L*W*H)**	
	PACKING	2.51kg ; 6pcs/15.15kg/0.86CUFT	


NOTE

1. All parameters NOT specially mentioned are measured at 230Vac input, rated load and 25℃ of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.
3. Tolerance :includes set up tolerance, line regulation and load regulation.
4. Derating may be needed under low input voltages. Please check the derating curve and Static characteristics for more details.
5. PV/PC functions when users do not use SVR.
6. Output will shut down after O/P voltage is below < 80% of Vset for 5 sec, re-power on to recover.
7. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 720mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies."
   (as available on https://www.meanwell.com//Upload/PDF/EMI_statement_en.pdf)
8. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft).


※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


BLOCK DIAGRAM




STATIC CHARACTERISTIC





EFFICIENCY VS LOAD (48V MODEL)




DERATING CURVE











LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


■ FUNCTION MANUAL

1.Output Voltage Programming (or, PV / remote voltage programming / remote adjust / margin programming / dynamic voltage trim)

※ In addition to the adjustment via the built-in potentiometer, the output voltage can be trimmed by applying EXTERNAL VOLTAGE.








◎ The rated current should change with the Output Voltage Programming accordingly.

2.Constant Current Programming (or, PC / remote current programming / dynamic current trim)

※ The output current can be trimmed to 20~100% of the rated current by applying EXTERNAL VOLTAGE.





◎ Output will shut down after O/P voltage is below < 80% of Vset for 5 sec, re-power on to recover.

※ Covered by over temperature protection, auto de-rating function works under operation either in PC mode or under control by communication protocol.

$T_{1(Typ.)}$: Maximum ambient temperature of full load.

$T_{2(Typ.)}$: T1+5℃.






LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.Remote ON-OFF Control


The power supply can be turned ON/OFF individually or along with other units in parallel by using the "Remote ON-OFF" function.



Remote ON-OFF	Power Supply Status
Short circuit	ON
Open circuit	OFF

4.DC-OK Signal

DC-OK signal is a TTL level signal. The maximum sink current is 10mA and the maximum external voltage is 5.6Vdc.



DC-OK signal	Power Supply Status
“High” >4.4~5.5Vdc	ON
“Low” <-0.5~0.5Vdc	OFF


5.Support CANBus or PMBus Communication

※ Communication provides function such as control, setting and monitorin , Parameters include output power, input voltage,ect.
For more details, please refer to: http://www.meanwell.com/manual.html

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

■ MECHANICAL SPECIFICATION

(Unit: mm , tolerance ±0.5mm) Case No.277A



• (tc) : Max. Case Temperature

AC Input Terminal(TB1) Pin NO. Assignment

Pin No.	Assignment	Terminal	Max mounting torque
1	AC/L	DECA T25	18Kgf-cm
2	AC/N		
3	⏚		

DC Output Terminal(TB2,TB3) Pin NO. Assignment

Pin No.	Assignment	Terminal	Max mounting torque
TB2	+Vo	(MW) HS455A	8Kgf-cm
TB3	-Vo		

※DIP SW:

Pin No.	Function	Description
1	A0	PMBus / CANBus interface address selectable.
2	A1	
3	A2	

※Control Pin No. Assignment(CN71) : HRS DF11-12DP-2DS or equivalent



Mating Housing	HRS DF11-12DS or equivalent
Terminal	HRS DF11-**SC or equivalent


Pin No.	Function	Description
1	PV	Connection for output voltage programming.(Note1)
2	PC	Connection for constant current level programming.(Note.1)
3,4	GND (Signal)	Negative output voltage signal.
5	Remote ON-OFF	The unit can turn the output ON/OFF by dry contact between Remote ON/OFF and 12V-AUX.(Note.2) Short (10.8dc ~ 13.2Vdc) : Power ON ; Open(0 ~ 0.5Vdc) : Power OFF ; The maximum input voltage is 13.2Vdc
6	DC-OK	Low (-0.5 ~ 0.5Vdc) : When the Vout≦80%±6%. High (4.4 ~ 5.5Vdc) : When Vout≧80%±6%. The maximum sourcing current is 10mA and only for output.(Note.2)
7,8	+12V-AUX	Auxiliary voltage output, 10.6~13.2Vdc, referenced to GND-AUX (pin9 & 10). The maximum load current is 0.4A. This output is not controlled by “Remote ON-OFF”.
9,10	GND-AUX	Auxiliary voltage output GND. The signal return is isolated from the output terminals (+V & -V).
11	SDA	For PMBus model: Serial Data used in the PMBus interface. (Note.2)
	CANH	For CANBus model: Data line used in CANBus interface. (Note.2)
12	SCL	For PMBus model: Serial Clock used in the PMBus interface. (Note.2)
	CANL	For CANBus model: Data line used in CANBus interface. (Note.2)


Note1: Non-isolated signal, referenced to [GND(signal)].
Note2: Isolated signal, referenced to GND-AUX.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Operate with additional aluminum plate

In order to meet the"Derating Curve"and the "Static Characteristics" ,UHP-1500 series must be installed onto an aluminum plate(or the cabinet of the same size) on the bottom.The size of the suggested aluminum plate is shown as below. And for optimizing thermal performance, the aluminum plate must have an even and smooth surface (or coated with thermal grease), and UHP-1500 series must be firmly mounted at the center of the aluminum plate.





Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000