75W AC/DC High-End Ultra Slim Industrial DIN Rail Power XDR-75 series



(XDR-75-xx)



(XDR-75-xxLA)



(XDR-75-xxPI)

(Applying) LISTED Class 1, Div. 2 (Applying) LISTED UL61010 BS EN/EN62368-1 BS EN/EN61558-1 BS EN/EN61010 IEC62368-1 IEC61558-1 IEC61010 (Note.5)

IS 13252 (By request Note.6) KC62368-1 (By request) CNS15598-1 GB4943.1 TPTC004

Automate Industrial Security Network Telecom

Features

- 85~305Vac input (277Vac available)
- Global certificates in multi-fields(ITE 62368-1,Industrial 61558-1/-2-16,61010) & Marine DNV,SEMI47,CID2 HazLoc approved
- 30mm ultra slim width
- High efficiency up to 91% and no load power dissipation 0.7W~1W by R.C.
- 200% peak power capability
- 600% transient peak current capability
- Built-in constant current limiting circuit
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Fanless design, cooling by free air convection
- Over voltage category III (OVC III)
- -40~+85°C wide range operation temperature(>+60°C derating)
- Operating altitude up to 5000 meters
- Built-in remote ON/OFF control and DC OK relay contact
- Ultra low inrush current <6~15A
- Tool free terminal block (LA Type)
- Conformal coating
- Can be installed on DIN rail TS-35/75 or15
- 5 years warranty

Applications

- Industrial control system
- Semiconductor fabrication equipment
- Factory automation
- Electro-mechanical apparatus

GTIN CODE

MW Search: https://www.meanwell.com/serviceGTIN.aspx

Description

The XDR-75 series is a 75W AC/DC high-end ultra slim industrial DIN rail power. Key features of this series include a narrow 30mm casing, optimizing system installation space, and an ultra-wide input range of 85~305Vac suitable for global use. It boasts a maximum efficiency of 91% and a low standby power consumption 0.7W~1W for energy savings and carbon reduction. It provides constant current with up to 200% peak power, and can handle instantaneous peak current of 600%. It has a fanless design, ultra-wide operating temperature range of -40 to +85℃ (up to +60℃ at full load); OVCIII compliance; ultra-low inrush current of <6~15A, and includes DC OK and remote ON/OFF functions. The internal PCB has a coating for basic moisture and dust protection, and it has multiple terminal blocks for selection. With comprehensive protection functions, complete safety certifications, and a 5-years warranty, the XDR-75 series is a compact, high-performance, and highly reliable DIN rail power supply.

Model Encoding

XDR - 75 - 24 ☐

- Output terminal type
- Output voltage(12V/24V/36V/48V)
- Output wattage
- Series name

Terminal Type Options		Note
Blank	Screw Terminal	In stock
LA	Lever Actuated	In stock
PI	Push In	In stock

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

75W AC/DC High-End Ultra Slim Industrial DIN Rail Power XDR-75 series

SPECIFICATION		XDR-75-12□	XDR-75-24□	XDR-75-36□	XDR-75-48□
		□ =Blank, LA, PI			
OUTPUT					
DC VOLTAGE		12V	24V	36V	48V
LOAD CURRENT RANGE		0 ~ 6.24A	0 ~ 3.12A	0 ~ 2.08A	0 ~ 1.56A
RATED POWER		74.88W	74.88W	74.88W	74.88W
PEAK	CURRENT (5sec.)	12.5A	6.25A	4.17A	3.13A
	POWER (5sec.)	150W			
RIPPLE & NOISE (max.) Note.2		100mVp-p	100mVp-p	120mVp-p	120mVp-p
VOLTAGE ADJ. RANGE		12 ~ 15V	24 ~ 29V	36 ~ 42V	48 ~ 56V
VOLTAGE TOLERANCE Note.3		±1.0%	±1.0%	±1.0%	±1.0%
LINE REGULATION		±0.5%	±0.5%	±0.5%	±0.5%
LOAD REGULATION		±1.0%	±1.0%	±1.0%	±1.0%
SETUP, RISE TIME		1200ms, 60ms/230Vac 2500ms, 60ms/115Vac at full load			
HOLD UP TIME (Typ.)		16ms/230Vac 10ms/115Vac at full load			
INPUT					
AC VOLTAGE RANGE		85 ~ 305Vac			
DC VOLTAGE RANGE		80 ~ 431Vdc (Derating 50% Load @80Vdc)			
NO LOAD CONSUMPTION(Typ.)	Remote Power OFF	0.7W @115Vac & 230Vac	1W @115Vac & 230Vac		
	Remote Power ON	1.5W @115Vac & 230Vac			
FREQUENCY RANGE		47 ~ 63Hz			
EFFICIENCY (Typ.)		89%	90%	91%	91%
AC CURRENT (Typ.)		1.5A/115Vac 0.9A/230Vac 0.8A/277Vac			
INRUSH CURRENT (Typ.)		COLD START 6A/115Vac 10A/230Vac 15A/277Vac			
LEAKAGE CURRENT		<1mA / 240Vac <1.5mA / 277Vac			
PROTECTION					
OVERLOAD		105%~200% rated output power for more than 5 sec then constant current limiting at rate current without shutdown when Vo=10%~100%; Constant current limiting or Latch mode when Vo<10% rated voltage.			
OVER VOLTAGE		16 ~ 19V	30 ~ 34V	43 ~ 50V	57 ~ 66V
		Protection type : Shut down o/p voltage , re-power on to recover			
OVER TEMPERATURE		Protection type : Shut down o/p voltage, recovers automatically after temperature goes down			
FUNCTION					
DC OK RELAY CONTACT		Relay Contact Ratings (max.):30Vdc/1A, 30Vac/0.5A resistive load			
REMOTE CONTROL		Power ON :RC + ~ RC- keep<0.5Vdc or open			
		Power OFF:RC + ~ RC- keep 4~5Vdc by external voltage			
TRANSIENT PEAK CURRENT CAPABLILTY		12V: 500% rated current for 4ms; 24V/36V/48V: 600% rated current for 4ms			
ENVIRONMENT					
WORKING TEMP.		-40 ~ +85℃ (Refer to "Derating Curve")			
WORKING HUMIDITY		20 ~ 95% RH non-condensing			
STORAGE TEMP., HUMIDITY		-40 ~ +85℃, 10 ~ 95% RH non-condensing			
TEMP. COEFFICIENT		±0.03%/℃ (0 ~ 60℃) on Load output			
VIBRATION		Component:10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6			

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

75W AC/DC High-End Ultra Slim Industrial DIN Rail Power XDR-75 series

SPECIFICATION	XDR-75-12□	XDR-75-24□	XDR-36□	XDR-48□
	□ =Blank, LA, PI			
SAFETY & EMC Note.4&5&6				
SAFETY STANDARDS	CB IEC62368-1, IEC61558-1/-2-16, IEC61010-1/-2-201 TUV BS EN/EN62368-1,BS EN/EN61558-1/-2-16,BS EN/EN61010-1/-2-201 UL UL121201/CSA C22.2 NO.213.17 Class I,DIV2 Group A,B,C,D Hazardous Locations T4;UL61010-1/-2-201 CCC GB4943.1 BSMI CNS15598-1 EAC TPTC004 Marine DNV SEMI F47 approved KC/BIS KC62368-1 and BIS IS 13252 (Part 1) certified, No stock ,contact sales by request			
OVER VOLTAGE CATEGORY Note.7	IEC/EN 61558-1/-2-16 (OVC Ⅲ, altitude up to 2000m) IEC/EN/UL 61010-1/-2-201 (OVC Ⅱ, altitude up to 5000m) IEC/EN 62368-1 (OVC Ⅱ, altitude up to 5000m)			
SAFETY EXTRA-LOW VOLTAGE(SELV)	IEC/EN 61558-2-16 (SELV) IEC/EN 62368-1 (SELV / ES1)			
WITHSTAND VOLTAGE	I/P-O/P: 4KVac I/P-FG: 2KVac O/P-FG: 1.5KVac O/P-DC OK: 0.5KVac			
ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG: 100M Ohms/500VDC/25℃/ 70%RH			
EMC EMISSION	**Parameter**	**Standard**	**Test Level / Note**	
	Conducted	BS EN/EN55032 (CISPR32) / BS EN/EN61204-3 / CNS15936 / KS C 9832	Class B	
	Radiated	BS EN/EN55032 (CISPR32) / BS EN/EN61204-3 / CNS15936 / KS C 9832	Class B	
	Harmonic Current	BS EN/EN61000-3-2	Class A	
	Voltage Flicker	BS EN/EN61000-3-3	-----	
EMC IMMUNITY	BS EN/EN55035 , BS EN/EN61204-3, BS EN/EN61000-6-2(BS EN/EN50082-2) ,KS C 9835,SEMI F47 tested at 200Vac			
	Parameter	**Standard**	**Test Level / Note**	
	ESD	BS EN/EN61000-4-2	Level 4, 15KV air ; Level 4, 8KV contact; criteria A	
	Radiated	BS EN/EN61000-4-3	Level 3, 10V/m ; criteria A	
	EFT / Burst	BS EN/EN61000-4-4	Level 4, 4KV ; criteria A	
	Surge	BS EN/EN61000-4-5	Level 4, 2KV/Line-Line ;Level 4, 4KV/Line-Line-Chassis ;criteria A	
	Conducted	BS EN/EN61000-4-6	Level 3, 10V ; criteria A	
	Magnetic Field	BS EN/EN61000-4-8	Level 4, 30A/m ; criteria A	
OTHERS				
MTBF	1907.3K hrs min. Telcordia SR-332 (Bellcore); 333.9K hrs min. MIL-HDBK-217F (25℃)			
DIMENSION	**30*125.2*116mm (W*H*D)**			
PACKING	496g; 24pcs/12.9Kg/1.27CUFT			

NOTE


1. All parameters NOT specially mentioned are measured at 230Vac input, rated load and 25℃ of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 μF & 47 μF parallel capacitor.
3. Tolerance : includes set up tolerance, line regulation and load regulation.
4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. (as available on https://www.meanwell.com//Upload/PDF/EMI_statement_en.pdf)
5. The Regulatory Compliance Mark (RCM) is applied on a voluntary basis. The equipment meets the relevant IEC or AS/NZS standards, or AS/NZS 3820 where applicable. The use of the RCM mark complies with AS/NZS 4417.1.
6. Some factory or model may not have the BIS logo, please contact your MEAN WELL sales for more information.
7. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft).
8. Installation clearances : 40mm on top, 20mm on the bottom, 5mm on the left and right side are recommended when loaded permanently with full power. In case the adjacent device is a heat source, 15mm clearance is recommended.

※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


■ Block Diagram

PWM fosc : 65KHz




■ Derating Curve


Suitable for 100/110/115/120Vac System (85~132Vac)




Suitable for 220/230/240/277Vac System (180~305Vac)



■ Output derating VS input voltage






Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

■ Peak Power

$$P_{av} = \frac{P_{pk} \times t + P_{npk} \times (T-t)}{T} \leqslant P_{rated}$$

$$Duty = \frac{t}{T} \times 100\% \leqslant 35\%$$

$t \leqslant 5$ sec



P_{av} : Average output power (W)


P_{pk} : Peak output power (W)

P_{npk} : Non-peak output power(W)

P_{rated} : Rated output power(W)

t : Peak power width(sec)

T : Period(sec)



For example (24V model) :

Vin = 200Vac Duty_max = 5%

$P_{av} = P_{rated} = 75W$

$P_{pk} = 150W$

$t \leqslant 5$ sec


$$T \geqslant \frac{5\ sec}{5\%} \geqslant 100sec$$

$$P_{npk} \leqslant \frac{T P_{av} - t P_{pk}}{T-t}$$

$P_{npk} \leqslant 71W$

■ Transient peak current Capability

The device can delivers peak currents over 2xIo capacity, sustained for several milliseconds.



Transient peak current voltage dip


Load	Vo(%)	12V	24V/36V/48V
		Time	Time
3xIo	75	6ms	8ms
4xIo	60	3ms	6ms
5xIo	40	2ms	5ms
6xIo	25	--	4ms

Note: The time indicated in the table refers to Power on AC for more than 3 seconds before applying load.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

■ Function Manual


Pin No.	Function	Description
1,2	DC OK Relay Contact	Contact close : PSU turns ON/DC_OK ; Contact open : PSU turns OFF/DC_fail; Contact ratings (max.): 30Vdc/1A ,30Vac/0.5A resistive load.
3	RC+	Turns the output ON and OFF by electrical signal Remote power ON : keep<0.5Vdc Remote power OFF: keep 4~5Vdc
4	RC-	




Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

1.DC OK Relay Contact

Contact Close	PSU turns ON / DC OK.
Contact Open	PSU turns OFF / DC Fail.
Contact Ratings (max.)	30Vdc/1A ,30Vac/0.5A resistive load.






External voltage source (U) and resistor (R)
(The max. Sink is 30Vdc/1A ,30Vac/0.5A)


Internal circuit of DC_OK, via relay contact

2.Remote ON/OFF Control

The PSU can be turned ON/OFF by using the "Remote Control" function.

PSU Vo Status	Between RC+(Pin3) and RC-(Pin 4)
Remote power ON	Keep<0.5Vdc or open
Remote power OFF	Keep 4~5Vdc by external voltage






R.C. by user's external auxiliary power.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

■ Mechanical Specification

(Unit:mm , Tolerance ±1mm)

Case No.301



Ⓐ : Terminal Pin No.Assignment

Pin No.	Assignment
1	DC Output +Vo
2,3	DC Output -Vo

Ⓑ : Control Pin No.Assignment

Pin No.	Assignment
1,2	DC OK Relay Contact
3	RC+
4	RC-

Ⓒ : Terminal Pin No.Assignment


Pin No.	Assignment
1	AC/L or DC Input +Vin
2	AC/N or DC Input -Vin
3	FG ⏚

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

■ Recommend Wiring

		AC Input T.B	DC Output T.B	Signal connector
Solid Wire		6mm² max.	6mm² max.	1.5mm² max.
A.W.G		16~10 AWG	16~10 AWG	24~16 AWG
Wire Stripping Length	Blank	10~11mm	10~11mm	8~9mm
	LA	11~12mm	11~12mm	
	PI	14~15mm	14~15mm	
Screw Terminal Torque	Blank	5 Lb-In	5 Lb-In	/
	LA/PI	Not applicable		

■ Installation Instruction



This series fits DIN rail TS35/7.5 or TS35/15.
For installation details, please refer to the Instruction manual.

ADMISSIBLE DIN-RAIL:TS35/7.5 OR TS35/15
(For reference only. Not included with unit.)

■ Installation Manual

Please refer to : http://www.meanwell.com/manual.html

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000