MEAN WELL

Your Reliable Power Partner







High Performance & Compact Design

Configurable Power Supply

450W~1200W Modular Series



2018 February

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Company Profile

Established in 1982, MEAN WELL is a leading standard switching power supply manufacturer in the world. MEAN WELL headquarters is in New Taipei Industrial Park, Taiwan, branches and sales offices at Guangzhou, Shenzhen, Suzhou in China, California USA, and Netherlands in the EU. Five production bases in New Taipei City (Taiwan), Huadu District in Guangzhou, Suzhou City in China, Bangalore in India and Kansas City in USA. The product lines include AC/DC switching power supplies, DC/DC converters, waterproof LED drivers, adaptors, DC/AC inverters and battery chargers. We have over 10,000 standard models widely used in medical, automation, communication, LED lighting, moving sign, and office automation applications.

With more than 40 years of experience in R&D and production of standard power supplies, MEAN WELL has ten product categories covering over 10,000 models, to provide "One Stop Shopping" power solutions. Every product in MEAN WELL is the result of rigid procedures governing design, design verification test (DVT), design quality test (DQT), component selection, pilot-run production, and mass production.

With more than 200 distributors globally, the MEAN WELL products are distributed to over 80 countries worldwide. The small size orders can expect delivery within 24 hours without MOQ requirement. If you are looking for switching power supply with high reliability, good quality, reasonable price and full series products, MEAN WELL, a total solution provider which can satisfy your various demands, is definitely your first choice!



MEAN WELL EUROPE




MEAN WELL SUZHOU



MEAN WELL TAIWAN



MEAN WELL USA



MEAN WELL INDIA




MEAN WELL MALAYSIA



MEAN WELL GUANGZHOU



MEAN WELL HONG KONG




MEAN WELL SINGAPORE



2xMOPP Introduction

MOPP stands for Mean of Patient Protection. It is the lastest requirement as per 60601-1 3rd edition. 2xMOPP means PSU with double insulation (DI) between Primary and Secondary sides and 1xMOPP between Primary to protective earth (FG) at normal condition. Shown as figure below. PSU with 2xMOPP can be implemented on almost **ALL** medical devices!



BF rated devices

Type BF (body floating) is generally used for applied parts that have conductive contact with the patient, or have medium or long term contact with the patient. Examples of this type of equipment are ultrasound scanner, blood pressure monitors, incubators and etc...


Medical laser


Operation lighting


Hospital bed

NMP Series

650W/1200W Intelligent Medical Modular Power Supply

Medical | 2xMOPP | BF rated | Industrial | Telecom

TAIWAN EXCELLENCE 2018 (NMP1K2)

Configurable

- Cover 3.3 to 55Vdc output range
- Modules can be in Parallel or Serial connection

Medical Applications

- 60601-1 Ed. 3 certified
- Touch current<100μA/264Vac

Intelligent Control

- Global & Local remote ON/OFF control
- DC OK signal
- T-Alarm (OT Waring signal for OTP)



Output Programmable

- PV range 50-100%
- PC range 40-100%

Others

- 90~264VAC
- Working temp.: -30~70°C
- Built-in DC fan
- 5 years warranty

Series Connection



Parallel Connection



Front View



Output Configuration Guide

ANSI/AAMI ES60601-1 | EN60601-1 | IEC60601-1

NMP □□□-□ □ □ □ □ □ □-□

SLOT 1 SLOT 2 SLOT 3 SLOT 4 SLOT 5 SLOT 6


650/1K2(650W/1200W)

Parallel or option code

For NMP1K2 only

NMP Series SPEC

MS-240 : 1-SLOT isolated single output (240W max.)

Picture	Item Code	Output	Vdc adj.	Tol.	R&N.	Max.
	C	5V, 0~36A	3~6V	±2%	100mV	180W
	E	12V, 0~20A	6~15V	±1%	150mV	240W
	H	24V, 0~10A	15~30V	±1%	150mV	240W
	K	48V, 0~5A	30~58V	±1%	250mV	240W

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



X-ray and
Image Diagnostic Machine



Automation Robot Arms

NMP Series Accessory

Parallel Connection Accessory

FAP-009 (for NMS-240, 2 units)	FAP-010 (for NMS-240, 3 units)	NMS-240-P2/P3/P4/P5/P6 (to parallel NMS-240 in 2/3/4/5/6 modules)
		

Series Connection Accessory

FAS-001 (for 1-slot modules: NMS-240)


Blank Plate Accessory

BLANK-NMS240




Medical Equipment
MRI Scanner



Telecommunication

MP Series


450W/650W/1000W Modular Power

Automate | Industrial | Telecom | Harsh

Industrial Applications
IEC/EN/UL 60950 certified

Output Adjustable
PV range ±5%

Remote Control
Remote ON/OFF control on single power module



Others
- 85~264VAC
- Protection: SCP, OLP, and fan fail alarm
- Cooling by build-in DC fan
- 3 years warranty

Configurable
- Cover 1.6 to 53Vdc output range with total 57 output modules
- Modules can be in Parallel or Serial connection

Output Configuration Guide

MP □-□ □ □ □ □ □ □ □-□

SLOT 1 SLOT 2 SLOT 3 SLOT 4 SLOT 5 SLOT 6 SLOT 7


- Parallel or option code
- For MP1K0 only
- Output wattage 450/650/1K0 (450/650/1000W)
- Modular Power with PFC

PFC c UL us UL60950-1 EN60950-1 CB CE

MP Series SPEC

MP Series Accessory

Parallel Connection Accessory

FAP-001	FAP-002	FAP-003	FAP-004
			
FAP-005	**FAP-006**	**FAP-007**	**FAP-008**
			

Series Connection Accessory

FAS-001	FAS-002	FAS-003	FAS-004
			



MS-75 : 1-SLOT single output (75W max.)



Item Code	L	M	N	O	P	Q
Output	3.3V, 0~15A	5V, 0~15A	12V, 0~6.3A	15V, 0~5.0A	24V, 0~3.2A	48V, 0~1.6A
Vdc adj.	2.6~4.0V	4.0~6.0V	9.0~13.2V	13.2~16.8V	20.0~26.4V	40.0~53.0V

MS-150 : 1-SLOT single output (150W max.)



Item Code	A	B	C	D	E	F	G	H	I	J	K
Output	2V, 0~25A	3.3V, 0~25A	5V, 0~25A	7.5V, 0~18A	12V, 0~13A	15V, 0~10A	18V, 0~8.5A	24V, 0~6.5A	27V, 0~5.8A	33V, 0~4.7A	48V, 0~3.2A
Vdc adj.	1.6~2.6V	2.6~4.0V	4.0~6.0V	6.0~9.0V	9.0~13.2V	13.2~16.8V	16.8~20.0V	20.0~26.4V	25.0~31.0V	30.0~40.0V	40.0~53.0V

MS-210 : 1-SLOT parallelable single output (210W max.)

※Parallel function up to 5 units



Item Code	1A	1B	1C	1D	1E	1F	1G	1H	1I	1J	1K
Output	2V, 0~35A	3.3V, 0~35A	5V, 0~35A	7.5V, 0~28A	12V, 0~17.5A	15V, 0~14A	18V, 0~11.6A	24V, 0~8.75A	27V, 0~7.8A	33V, 0~6.4A	48V, 0~4.4A
Vdc adj.	1.6~2.6V	2.6~4.0V	4.0~6.0V	6.0~9.0V	9.0~13.2V	13.2~16.8V	16.8~20.0V	20.0~26.4V	25.0~31.0V	30.0~40.0V	40.0~53.0V

MS-300 : 2-SLOT parallelable single output (300W max.)

※Parallel function up to 3 units



Item Code	2A	2B	2C	2D	2E	2F	2G	2H	2I	2J	2K
Output	2V, 0~50A	3.3V, 0~50A	5V, 0~50A	7.5V, 0~40A	12V, 0~25A	15V, 0~20A	18V, 0~16.7A	24V, 0~12.5A	27V, 0~11.2A	33V, 0~9.1A	48V, 0~6.3A
Vdc adj.	1.6~2.6V	2.6~4.0V	4.0~6.0V	6.0~9.0V	9.0~13.2V	13.2~16.8V	16.8~20.0V	20.0~26.4V	25.0~31.0V	30.0~40.0V	40.0~53.0V

MS-360 : 2-SLOT parallelable single output (360W max.)

※Parallel function up to 3 units



Item Code	3A	3B	3C	3D	3E	3F	3G	3H	3I	3J	3K
Output	2V, 0~60A	3.3V, 0~60A	5V, 0~60A	7.5V, 0~48A	12V, 0~30A	15V, 0~24A	18V, 0~20A	24V, 0~15A	27V, 0~13.4A	33V, 0~11A	48V, 0~7.5A
Vdc adj.	1.6~2.6V	2.6~4.0V	4.0~6.0V	6.0~9.0V	9.0~13.2V	13.2~16.8V	16.8~20.0V	20.0~26.4V	25.0~31.0V	30.0~40.0V	40.0~53.0V

MD-100 : 1-SLOT isolated dual output (100W max.)




Item Code	R	S	T	U	V	W	X
Output	5V, 2.0~10A 5V, 0.0~8.0A	5V, 2.0~10A 12V, 0.0~5.8A	5V, 2.0~10A 15V, 0.0~4.7A	24V, 0.5~3.0A 5V, 0.0~10A	24V, 0.6~3.0A 12V, 0.0~4.7A	12V, 1.0~5.0A 12V, 0.0~5.8A	15V, 1.0~4.7A 15v, 0.0~4.7A
Vdc adj.	4.75~5.5V 4.75~5.5V	4.75~5.5V 11.4~13.2V	4.75~5.5V 14.2~16.5V	22.8~26.4V 4.75~5.5V	22.8~26.4V 11.4~13.2V	11.4~13.2V 11.4~13.2V	14.2~16.5V 14.2~16.5V

Common Features for MP&NMP

Modular Power Design

Easy configurable design, offer the most flexible power solutions.



Programmable Output Function

Output voltage is adjustable. By using external DC signal, output voltage can be tuned up or down according to end user's need.

NMP Series



PV range: 50%-100%
PC range: 40%-100%

MP Series




PV range: ±5%

Multiple Application

MP and NMP series cover wide output voltage range. MP series covers 1.6~53 Vdc, and NMP series covers 3~55 Vdc. Furthermore, with parallel and series connection function, both series can easily meet various power requirements.



NMP+MP Series



Medical Equipment



Industrial Automation



Tele-communication


Compact Dimension

NMP Series

Dimensions(LxWxH):

- NMP650: 250x 89x 41mm
- NMP1K2: 250x 127x 41mm





MP Series

Dimensions(LxWxH):

- MP450: 254x 127x 63.5mm
- MP650: 278x 127x 63.5mm
- MP1K0: 278x 177.8x 63.5mm

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

New for NMP Series

Intelligent Control


NMP Series features remote ON/OFF, DC OK signal output, T-alarm signal output, and PC & PV output programmable functions to enable system with smart monitoring and handy control over power supply.

Remote ON/OFF

With Global and Local ON/OFF control, it allows user to turn on all modules at once or turn on specific module.

T-alarm


By adopting this new feature, PSU can send out over-temperature alert thru TTL signal to system warning possible over-heating event.



Easy Inventory Management

NMP Series has a lean product line-up with merely 2 front-ends and 4 power modules in total. Inventory management is no longer a difficult job for distributors!

NMS-240



x 4

MS-75/150/210/300/360

MD-100



x 57

1U Low Profile

MEAN WELL design engineers implement the latest technology to make possible NMP Series in a slim size. NMP Series successfully reduces nearly 60% in size compared with its predecessor MP Series. Thanks to its smaller size, NMP Series can be used on applications that space constraint is a critical concern to system design.

60%



Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Assembly Illustration for NMP Series

Product Description

Configurable type power supply, NMP family, is a 1U low profile modular power. This family comprises two models, NMP650 (650W) and NMP1K2 (1200W). To offer wide application aspects, NMP family complies with medical standards safety approval and its design refers to ITE standards. Furthermore, by applying safety approvals on Front-End (NMP650 & NMP1K2) and power modules (NMS-240) respectively, distributors whose technical and service capability being qualified by MEAN WELL might be officially authorized to assemble NMP power systems according to end customers' requirements.

Remove screws from left and right sides of the case. And detach the top cover.



STEP 1

Install modules to NMP1K2/NMP650 Front-End in the order from right to left.
5V / 12V / 24V / 48V modules are aviliable for choice.



STEP 2


Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Put back the top cover and fasten screws to positions as illustration.



STEP 3

Stick corresponding product model label onto top cover of Front-End.



(For illustration only, model number might not fully conform with product configuration in photo.)

STEP 4

Apply AC power to NMP1K2 / NMP650 and measure output voltage to ensure each module functions properly.
Use two 2-unit parallel cooper plates, FAP-009, to connect +V and –V terminals of slot 1 and slot 2, and use accessory cable to parallel GND pins and signals when modules in parallel.



STEP 5

Welcome to scan QR codes for more product information.

Introduction Video

Assembly Video

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Taiwan (Headquarters)
MEAN WELL ENTERPRISES CO., LTD.
No. 28, Wuquan 3rd Road, Wugu District,
New Taipei City, Taiwan, 24891
Tel +886-2-2299-6100(rep.)
e-mail info@meanwell.com
Web www.meanwell.com

U.S.A.
MEAN WELL USA, INC.
44030 Fremont Blvd., Fremont, CA 94538, U.S.A.
Tel +1-510-683-8886
e-mail info@meanwellusa.com
Web www.meanwellusa.com

Europe
MEAN WELL EUROPE N.V.
Langs de Werf 8, 1185XT Amstelveen, the Netherlands
Tel +31-20-758-6000
e-mail info@meanwell.eu
Web www.meanwell.eu



info@meanwell.com
www.meanwell.com

China
MEAN WELL (GUANGZHOU) ELECTRONICS CO., LTD.
No.11, Jingu South Road, Huadong Town, Huadu Distric,
Guangzhou, Guangdong, China
Tel +86-20-3773-7100 / 400-800-3608(sales)
+86-10-5200-1817(Beijing Office)
+86-755-2359-1630(Shengzhen Office)

SUZHOU MEAN WELL TECHNOLOGY CO., LTD.
No.269, Changping Road, Huangdai Town, Xiangcheng District,
Suzhou, Jiangsu Province, China
Tel +86-512-6508-8600 **e-mail** info@meanwell.cc
Web www.meanwell.cc

MEAN WELL (HONG KONG) HOLDING LIMITED
Unit 1112, 11/F., Concordia Plaza, 1 Science Museum Road,
Tsim Sha Tsui, Kowloon, Hong Kong
Tel +852-2643-9098 **e-mail** vickiho@meanwell.com.hk
Web www.meanwell.com.hk

INDIA
MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED
Plot No. 9C, GF-1F, Peenya Industrial Area, 2nd Phase, Chokkasandra
Main Road, Bengaluru-560058
Tel +91-8068728613 **e-mail** info@meanwellindia.com
Web www.meanwellindia.com

PRINTED WITH SOY INK

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000